

EFFEKT ECOSUND® CEILING/WALL

Effekt EcoSUND Ceiling/Wall with clamp is an excellent sound absorbent for all types of environments. Made of EcoSUND and can be chosen in raw EcoSUND or dressed in textile.

PRESCRIBED TEXT

EFFEKT CEILING/WALL

Sound absorbent in EcoSUND that is mounted with clamps.

Thickness: 50 mm.

Measurements 1200x600 alt 1200x900.

Choice: Clamp with our without air space.

Raw: white, black, grey or light grey.

Dressed: Hush xxx (edge in raw colour).

Fire test of EcoSUND: EcoSUND is tested according to EN 13501-11:2007 + A1 2009, EN 13823 and EN ISO 1925-2 with approvd raiting B-s1,d0*.

* Also tested with polyester surface layer material and Trevira CS.

For updated information, see https://www.gotessons.com/en/products/wall-and-ceiling-absorbents/effekt-ecosound%C2%AE-ceiling-wall

ARTICLES

ART. NO	SIZE / DESCRIPTION	Color	W:	H:	D:
125130-	Effekt EcoSUND Ceiling/Wall	raw	1200	600	50
125131-	Effekt EcoSUND Ceiling/Wall	dressed	1200	600	50
125132-	Effekt EcoSUND Ceiling/Wall	raw	1200	900	50
125133-	Effekt EcoSUND Ceiling/Wall	dressed	1200	900	50
125134-	Effekt EcoSUND ceiling/wall	dressed	1200	1200	50