

Götessons Industri AB
Box 56
523 22 ULRICEHAMN
SWEDEN

Testing of screens for office use

(3 appendices)

Customer:	Götessons Industri AB
Test object/ID:	Table mounted screen / Screen It AT40
Test method:	Möbelfakta requirements specification 2016-07-01 for table-mounted screens EN 1023-2:2000 Office furniture - Screens - Mechanical safety requirements EN 1023-3:2000 Office furniture - Screens - Test methods EN 1023-1:1996: Office furniture - Screens - Dimensions
Test environment:	23 ± 2°C and 50 ± 5% relative humidity
Scope:	Complete test
Date of test:	2019-04-10
Test result:	The tested object passed the test
Reservation:	The test results in this report apply solely to the specimen tested

RISE Research Institutes of Sweden AB Building Technology - Wood Technological Assessment

Performed by

Examined by

Robert Almqvist

Bengt-Åke Andersson

Appendices

1. Test result (2 pages)
2. Description of test object (1 page)
3. Pictures (2 pages)

RISE Research Institutes of Sweden AB

Postal address	Office location	Phone / Fax / E-mail
Box 857 SE-501 15 BORÅS Sweden	Brinellgatan 4 SE-504 62 BORÅS	+46 10 516 50 00 +46 33 13 55 02 info@ri.se

This report may not be reproduced other than in full, except with the prior written approval of the issuing laboratory.

Appendix 1

Test result

Abbreviations: N/A = Not applicable
N/T = Not tested

Table 1

	Requirements	Method	Cycles	Load	Results
1.1	Horizontal static force on table mounted screen (100 mm from top edge of screen)	EN 14074 6.3.2	10	80 N	Pass
1.2	Functional test Vertical static force on table mounted screen (100 mm from the edge)	Möbelfakta Requirements Specification 2016-07-01	10	200 N	Pass
1.3	Safety test Vertical static force on table mounted screen (100 mm from the edge)	Möbelfakta Requirements Specification 2016-07-01	10	300 N	Pass
1.4	Stability for non-load bearing screens Screen displacement 200 mm	EN 1023-3 6.1	1	Max 200 N	N/A
1.5	Stability for load bearing screens Screen displacement 200 mm	EN 1023-3 6.2	1	Max 200 N	N/A
1.6	Dislodgement test for screen mounted components Work surface Other components 100 N	EN 1023-3 6.3	1 1	200 N 100 N	N/A N/A
1.7	Loadbearing screens Load = 2 times the manufacturer's maximum recommended weight	EN 1023-3 6.4	1 24h		N/A
1.8	Edges and corners of the screen with which the user comes into contact are rounded and free from burrs. Ends of hollow components are closed or capped. Movable and adjustable parts are so designed that injuries and inadvertent operation are avoided. The manufacturer shall indicate in his instruction manual how to use the screen in combination with add-on elements, as well as the admissible load for each type of screen.	EN 1023-2 3.			Pass

Appendix 1

Note. For table mounted screens:

The classification assumes that the screen is mounted on a table with a height of 720 mm

The screen height above of the table top is 500 mm

It causes a screen height of 1220 mm (500+720 mm)

Table 2

1.	Dimension	EN 1023-1	Classification
1.	Eye contact in the sitting position: Height \leq 1100 mm	2.1	
1.2	No eye contact in the sitting position: Height \geq 1400 mm	2.1	
1.3	Eye contact in the standing position: Height \leq 1400 mm	2.1	X
1.4	No eye contact in the standing position: Height \geq 1800 mm	2.1	

Appendix 2

Description of test object

Test object/ID: Table mounted screen / Screen It AT40

Dimensions

Height: 450 mm
Width: 1800 mm
Thickness /depth: 40 mm
Mass: 8.3 kg

Components

Core: MDF core with sound absorbing material on either side
Upholstery: Fabric
Screen attachment: Desk clamp

Sampling: The test object was selected by the customer
Date of arrival at
RISE test laboratory: 2019-04-09
Observed defects before testing: No defects

Appendix 3

Pictures




Figure 1




Figure 2

Appendix 3



Figure 3